Taskmaster CUH-Electric Unit Heater





APPLICATIONS

Heavy duty unit heaters for horizontal or vertical mounting. Ideal for space heating of larger areas such as warehouses, open plan stores, sports halls, factories and workshops. Also for anti-condensation heating in plant rooms. When mounted with vertical discharge, can be used to recirculate high level hot air for improved heating efficiency.

FEATURES

- Rugged heavy duty finned metal sheathed elements
- Totally enclosed permanently lubricated motor for increased reliability
- Automatic reset over temperature cut out for added safety
- Fan delay switch to purge unit of residual heat on switch off
- Draw through design for efficient air circulation
- Adjustable directional louvres for optimum airflow
- Flexibility of horizontal or vertical mounting

CAT No. Integral contactor	Output: kW	Output: Volts	Heater Length (mm)	Heater Height (mm)	Heater Depth (mm)	Max horiz mount hgt(m)	Max vert mount hgt(m)	Weight (kg)	Trade Price
CUH-03-1C	3.3	230	368	450	165	2.8	2.8	12	£615
CUH-03-3C	3.3	400	368	450	165	2.8	2.8	12	£630
CUH-05-1C	5	230	368	450	165	2.8	2.8	12	£660
CUH-05-3C	5	400	368	450	165	2.8	2.8	12	£685
CUH-07-3C	7	400	546	620	165	3	3.7	23	£750
CUH-10-3C	10	400	546	620	165	3	4.3	23	£860
CUH-15-3C	15	400	546	730	165	3.4	5.5	30	£1385
CUH-20-3C	20	400	743	865	256	3.7	6.7	55	£1775
CUH-25-3C	25	400	743	865	256	3.7	6.7	55	£2080
CUH-30-3C	30	400	743	865	256	3.7	6.1	55	£2400
син-тн	Integral thermostat (Range: 10-32°C)			£85	CUH-C2550	Wall bracket (20-40kW) - horizontal airflow			£90
CUH-DTH	Integral De-stratification thermostat			£80	CUH-VB35	Vertical bracket (3-5kW) - vertical airflow			£80
CUH-RTH	Remote thermostat	£80	CUH-VB720	Vertical bracket (7.5-20kW) - vertical airflow					
CUH-FSW	Fan Only Switch	£60	CUH-V2550	Vertical bracket (25-30kW) - vertical airflow					
CUH-C35	Wall bracket (3-5kW) - horizontal airflow			£60	CUH-EYE	Eye-bolt set	for chain susper	nsion	£55
CUH-C720	Wall bracket (7.5-15	£80							

Control Options available on page 28